SHOWER DOOR HINGES 700 SERIES

700 SERIES OF **HINGES:**

700 Series of Hinges are designed with beveled edges and radius corners for a sleek appearance. They can be used to support 8-12mm (5/16"-1/2") thick safety glass in swinging door installations.
*NOTES: SAME SHAPE
HINGES MADE OF
STAINLESS STEEL ARE
AVAILABLE.



■ **Hinge Size:** 90x55mm(3-9/16"x2-3/16")

Construction: Solid Brass

Hinge Swings: 90° in and 90° out.

Closing Type: Self-Centering when within 25° of closed position

Cut-out Required

Standard Scope of Supply Includes: Gaskets, Self Drilling Screws & Plastic Anchor Bolts for Wall Mount Hinges and Glass Cut Out Drawing.

Standard Finishes:

CP (Bright Chrome), BN (Brushed Nickel), SCP (Satin Chrome), AB (Antique Brass), PB (Polished Brass), ORB (Oil Rubbed Bronze), GM (Gun Metal), Ti (Titanium plated), PVD.

Maximum Capacities

Quantity of Hinges	Door Weight	Door Width
Using 2 Hinges	40kg(901bs)	760mm(30")
Using 3 Hinges	55kg(1201bs)	820mm(32")
NOTE D	1 1	

*NOTE:Do not exceed maximum door weight or width when choosing proper quantity of hinges

Reversible 5° pivot pin is available on request.








722

Wall Mount Hinge, Offset Back Plate



730 180° Glass to Glass Hinge



732 135° Glass to Glass Hinge





734 90° Glass to Glass Hinge





SHOWER DOOR HINGES 700-20 SERIES



720-20
Wall Mount Hinge,
Full Back Plate
720-20 HP
With H Back Plate
720-20 SP
With Short Back Plate
722-20
Wall Mount Hinge
Offset Back Plate



730-20 180° Glass to Glass Hinge



732-20 135° Glass to Glass Hinge



734-20 90° Glass to Glass Hinge

700-20 SERIES OF HINGES

700-20 Series of Hinges are designed with beveled edges and radius corners. The Special Feature is that the hinges are adjustable to any angle up to 90 degree without having to take door down. They can be used to support 8-12mm (5/16''-1/2'')thick safety glass in swinging door installations.



Hinge Size:

90x55mm(3-9/16"x2-3/16"

Construction:

Solid Brass

Hinge Swings:

90° in and 90° out (at factory set position).

Closing Type:

Self-Centering when within 25° of closed position.

- Cut-out Required
- Standard Scope of Supply Includes:

Gaskets, Self Drilling Screws & Plastic Anchor Bolts for Wall Mount Hinges and Glass Cut Out Drawing.

Standard Finishes:

CP (Bright Chrome), BN (Brushed Nickel), SCP (Satin Chrome), BSCP (Brushed Satin Chrome), AB (Antique Brass), PB (Polished Brass), ORB (Oil Rubbed Bronze), GM (Gun Metal), Ti(Titanium plated), PVD.

Maximum Capacities

Quantity of Hinges	Door Weight	Door Width
Using 2 Hinges	36kg(80lbs)	711mm(28")
Using 3 Hinges	54kg(120lbs)	813mm(32")




SHOWER DOOR HINGES 700-1 SERIES

720-1
Wall Mount Hinge,
Full Back Plate
720-1 HP
With H Back Plate
720-1 SP
With Short Back Plate



722-1
Wall Mount Hinge,
Offset Back Plate



730-1 180° Glass to Glass Hinge



732-1 135° Glass to Glass Hinge

700-1 SERIES OF HINGES

700-1 Series of Hinges are designed with straight edges and straight corners. They can be used to support 8-12mm (5/16"-1/2") thick safety glass in swinging door installations.
*NOTES: SAME SHAPE HINGES MADE OF STAINLESS STEEL ARE AVAILABLE.

SPECIFICATIONS:

Hinge Size:

90x55mm(3-9/16"x2-3/16")

Construction:

Solid Brass

Hinge Swings:

90° in and 90° out.

Closing Type:

Self-Centering when within $25\,^\circ$ of closed position

Cut-out Required

Standard Scope of Supply Includes:

Gaskets, Self Drilling Screws & Plastic Anchor Bolts for Wall Mount Hinges and Glass Cut Out Drawing.

Standard Finishes:

CP (Bright Chrome), BN (Brushed Nickel), SCP (Satin Chrome), BSCP (Brushed Satin Chrome), AB (Antique Brass), PB (Polished Brass), ORB (Oil Rubbed Bronze), GM (Gun Metal), Ti(Titanium plated), PVD.

Maximum Capacities

Quantity of Hinges	Door Weight	Door Width
Using 2 Hinges	40kg(90lbs)	760mm(30")
Using 3 Hinges	55kg(120lbs)	820mm(32")

*NOTE: Do not exceed maximum door weight or width when choosing proper quantity of hinges

when choosing proper quantity of hinges ■ Reversible 5° pivot pin is available on request.



732-1WG 135° Wall Mount Hinge



734-1 90° Glass to Glass Hinge



SHOWER DOOR HINGES 700-21 SERIES



700-21 SERIES OF HINGES:

700-21 Series of Hinges are designed with straight edges and straight corners. The Special Feature is that the hinges are adjustable to any angle up to 90 With Short Back Plate degree without having to take door down. They can be used to support 8-12mm (5/16''-1/2'')thick safety glass in swinging door installations.



720 - 21Wall Mount Hinge,

Full Back Plate

720-21 HP With H Back Plate 720-21 SP

722-21

Wall Mount Hinge, Offset Back Plate available



730-21180° Glass to Glass Hinge

SPECIFICATIONS:

Hinge Size:

90x55mm(3-9/16"x2-3/16")

Construction:

Solid Brass

Hinge Swings:

90° in and 90° out (at factory set position)

Closing Type:

Self-Centering when within 25° of closed position

- Cut-out Required
- Standard Scope of Supply Includes:

Gaskets, Self Drilling Screws & Plastic Anchor Bolts for Wall Mount Hinges and Glass Cut Out Drawing.

Standard Finishes:

CP (Bright Chrome), BN (Brushed Nickel), SCP (Satin Chrome), BSCP (Brushed Satin Chrome), AB (Antique Brass), PB (Polished Brass), ORB (Oil Rubbed Bronze), GM (Gun Metal), Ti (Titanium plated), PVD.

Maximum Capacities

Quantity of Hinges	Door Weight	Door Width
Using 2 Hinges	36kg(80lbs)	711mm(28")
Using 3 Hinges	54kg(120lbs)	813mm(32")

*NOTE:Do not exceed maximum door weight or width when choosing proper quantity of hinges



732-21 135° Glass to Glass Hinge



734-21 90° Glass to Glass Hinge

SHOWER DOOR HINGES 750 SERIES



750 with beveled edges and radius corners



750-1 with straight edges and straight corners



750-2 with rounded design.

750 SERIES OF HINGES:

750 Series of Hinges are Pivot Hinges designed for Top and Bottom Mount. There are three different shapes: With beveled edges and radius corners (750), With straight edges and straight corners (750-1), Rounded design (750-2) They can carry the majority of the weight on the bottom. They can be used to support 8-12mm (5/16''-1/2'') thick safety glass in swinging door installations.



SPECIFICATIONS:

Construction:

Solid Brass

Hinge Swings:

Full Rotation (360°)

Closing Type:

Self-Centering when within 25° of closed position

Cut-out Required

Standard Scope of Supply Includes:

Gaskets, Self Drilling Screws & Plastic Anchor Bolts for Floor/Ceiling Mount hinges and Glass Cut Out Drawing.

Standard Finishes:

CP (Bright Chrome), BN (Brushed Nickel), SCP (Satin Chrome), BSCP (Brushed Satin Chrome), AB (Antique Brass), PB (Polished Brass), ORB (Oil Rubbed Bronze), GM (Gun Metal), Ti(Titanium plated), PVD.

Maximum Capacities

Quantity of Hinges	Door Weight	Door Width
Using 2 Hinges	45kg(100lbs)	787mm(31")
J.MOTE D	1 1	. 1 .



SHOWER DOOR HINGES 700-8 SERIES



720-8 Wall Mount Hinge, Full Back Plate

722-8
Wall Mount Hinge
Offset Back Plate
available.



730-8 180° Glass to Glass Hinge



732-8 135° Glass to Glass Hinge



734-8 90° Glass to Glass Hinge

700-8 SERIES OF HINGES

700-8 Series of
Hinges are designed
with straight edges
and radius corners.
They can be used to
support 8-12mm
(5/16"-1/2")
thick safety
glass in swinging door
installations
*NOTES:SAME SHAPE
HINGES MADE OF
STAINLESS STEEL
ARE AVAILABLE.

SPECIFICATIONS:

Hinge Size:

90x55mm(3-9/16"x2-3/16")

Construction:

Solid Brass

Hinge Swings:

90° in and 90° out.

Closing Type:

Self-Centering when within 25° of closed position

Cut-out Required

Standard Scope of Supply:

Gaskets, Self Drilling Screws & Plastic Anchor Bolts for Wall Mount Hinges and Glass Cut Out Drawing.

Standard Finishes:

CP (Bright Chrome), BN (Brushed Nickel), SCP (Satin Chrome), BSCP (Brushed Satin Chrome), AB (Antique Brass), PB (Polished Brass), ORB (Oil Rubbed Bronze), GM (Gun Metal), Ti (Titanium plated), PVD.

Maximum Capacities

Quantity of Hinges	Door Weight	Door Width
Using 2 Hinges	40kg(90lbs)	760mm(30")
Using 3 Hinges	55kg(120lbs)	820mm(32")

*NOTE:Do not exceed maximum door weight or width when choosing proper quantity of hinges

■ Reversible 5° pivot pin is available on request.

SHOWER DOOR HINGES 700-9 SERIES



720-9
Wall Mount Hinge,
Full Back Plate
722-9
Wall Mount Hinge,
Offset Back Plate



730-9 180° Glass to Glass Hinge



732-9 135° Glass to Glass Hinge



734-9 90° Glass to Glass Hinge

700-9 SERIES OF HINGES:

700-9 Series of Hinges are designed with curved surfaces and sleek edges providing elegancy and vividness to glass shower enclosures. They can be used to support 8-12mm (5/16"-1/2") thick safety glass in swinging door installations.

SPECIFICATIONS:

■ **Hinge Size:** 90x56mm(3-9/16"x2-3/16")

■ Construction: Solid Brass

Hinge Swings: 90° in and 90° out.

Closing Type:

Self-Centering when within 25° of closed position

Cut-out Required

Standard Scope of Supply Includes:

Gaskets, Self Drilling Screws & Plastic Anchor Bolts for Wall Mount Hinges and Glass Cut Out Drawing.

Standard Finishes:

CP (Bright Chrome), BN (Brushed Nickel), SCP (Satin Chrome), BSCP (Brushed Satin Chrome), AB (Antique Brass), PB (Polished Brass), ORB (Oil Rubbed Bronze), GM (Gun Metal), Ti (Titanium plated), PVD.

Maximum Capacities

Quantity of Hinges	Door Weight	Door Width
Using 2 Hinges	40kg(90lbs)	760mm(30")
Using 3 Hinges	55kg(120lbs)	820mm(32")



SHOWER DOOR HINGES 700-7 SERIES



720-7 Wall Mount Hinge, Full Back Plate

722-7
Wall Mount Hinge,
Offset Back Plate
available



730-7 180° Glass to Glass Hinge



732-7 135° Glass to Glass Hinge



734-7 90° Glass to Glass Hinge

700-7 SERIES OF HINGES

700-7 Series of Hinges are designed with curved surfaces and straight corners, providing elegancy and vividness to glass shower enclosures. They can be used to support 8-12mm (5/16"-1/2") thick safety glass in swinging door installations.

SPECIFICATIONS:

Hinge Size:

90x55mm(3-9/16"x2-3/16")

Construction:

Solid Brass

Hinge Swings:

90° in and 90° out.

Closing Type:

Self-Centering when within $25\,^\circ$ of closed position

Cut-out Required

Standard Scope of Supply:

Gaskets, Self Drilling Screws & Plastic Anchor Bolts for Wall Mount Hinges and Glass Cut Out Drawing.

Standard Finishes:

CP (Bright Chrome), BN (Brushed Nickel), SCP (Satin Chrome), BSCP (Brushed Satin Chrome), AB (Antique Brass), PB (Polished Brass), ORB (Oil Rubbed Bronze), GM (Gun Metal), Ti(Titanium plated), PVD.

Maximum Capacities

Quantity of Hinges	Door Weight	Door Width
Using 2 Hinges	40kg(90lbs)	760mm(30")
Using 3 Hinges	55kg(120lbs)	820mm(32")

*NOTE:Do not exceed maximum door weight or width when choosing proper quantity of hinges

lacksquare Reversible 5° pivot pin is available on request.



SHOWER DOOR HINGES 700-6 SERIES



720-6 Wall Mount Hinge H Back Plate



730-6 180° Glass to Glass Hinge



732-6 135° Glass to Glass Hinge

700-6 SERIES OF HINGES

700-6 Series of Hinges are designed with straight edges and straight corners with delicate appearance. They can be used to support 8-12mm (5/16"-1/2") thick safety glass in swinging door installations.



SPECIFICATIONS:

Hinge Size:

 $89 \times 50 \text{mm} (3-1/2" \times 1-15/16")$

Construction:

Solid Brass

Hinge Swings:

90° in and 90° out.

Closing Type:

Self-Centering when within 15° of closed position

Cut-out Required

Standard Scope of Supply Includes:

Gaskets, Self Drilling Screws & Plastic Anchor Bolts for Wall Mount Hinges and Glass Cut Out Drawing.

Standard Finishes:

CP (Bright Chrome), BN (Brushed Nickel), SCP (Satin Chrome), BSCP (Brushed Satin Chrome), AB (Antique Brass), PB (Polished Brass), ORB (Oil Rubbed Bronze), GM (Gun Metal), Ti (Titanium plated), PVD.

Maximum Capacities

Quantity of Hinges	Door Weight	Door Width
Using 2 Hinges	36kg(80lbs)	720mm(28")for 10mm thick glass 660mm(26") for 12mm thick glass
Using 3 Hinges	54kg(120lbs)	820mm(32")for 10mm thick glass 760mm(30") for 12mm thick glass



SHOWER DOOR HINGES 700-5 SERIES



Wall Mount Hinge

720-5T
Top Mount Hinge
720-5B
Bottom Mount Hinge



180° Glass to Glass Hinge

730-5T
Top Mount Hinge
730-5B
Bottom Mount Hinge



135° Glass to Glass Hinge 732-5T Top Mount Hinge 732-5B Bottom Mount Hinge



90° Glass to Glass hinge

734-5T
Top Mount Hinge
734-5B
Bottom Mount Hinge

700-5 SERIES OF HINGES

700-5 Series of Hinges are designed specially for corner mounting, Each style has one bottom mount hinge and one top mount hinge.
Order should be made for pairs of hinges. They can be used for 8-12mm (5/6"-1/2") thick tempered safety glass.



SPECIFICATIONS:

Hinge Size:

 $108 \times 55 \text{mm} (4-1/4" \times 2-3/16")$

Construction:

Solid Brass

Hinge Swings:

90° in and 90° out.

Closing Type:

Self-Centering when within 25° of closed position

Cut-out and Hole Required

Standard Scope of Supply Includes:

Gaskets, Self Drilling Screws & Plastic Anchor Bolts for Wall Mount Hinges and Glass Cut Out Drawing.

Standard Finishes:

CP (Bright Chrome), BN (Brushed Nickel), SCP (Satin Chrome), BSCP (Brushed Satin Chrome), AB (Antique Brass), PB (Polished Brass), ORB (Oil Rubbed Bronze), GM (Gun Metal), Ti(Titanium plated), PVD.

Maximum Capacities

Quantity of Hinges	Door Weight	Door Width
Using 2 Hinges	40kg(90lbs)	800mm(31.5")
Using 3 Hinges	61kg(135lbs)	890mm(35")

SHOWER DOOR HINGES 700-4 SERIES


700-4 SERIES OF HINGES

700-4 Series of Hinges have rectangular design with straight edges and round corners provide bigger mounting surface on glass to provide superior support and can be also side mounted at top and bottom corners of the door besides anywhere in-between. They can be used for 8-12mm (5/16''-1/2'') thick tempered safety glass.



720-4

Wall Mount Hinge 722-4 Wall Mount Hinge, Offset Back Plate Available on request



730-4 180° Glass to Glass Hinge

SPECIFICATIONS:

Hinge Size:

 $110 \times 60 \text{mm} (4-5/16" \times 2-3/8")$

Construction:

Solid Brass

Hinge Swings:

90° in and 90° out.

Closing Type:

Self-Centering when within 25° of closed position

Cut-out and Hole Required

Standard Scope of Supply Includes:

Gaskets, Self Drilling Screws & Plastic Anchor Bolts for Wall Mount Hinges and Glass Cut Out Drawing.

Standard Finishes:

CP (Bright Chrome), BN (Brushed Nickel), SCP (Satin Chrome), BSCP (Brushed Satin Chrome), AB (Antique Brass), PB (Polished Brass), ORB (Oil Rubbed Bronze), GM (Gun Metal), Ti(Titanium plated), PVD.

Maximum Capacities

Quantity of Hinges	Door Weight	Door Width
Using 2 Hinges	40kg(90lbs)	800mm(31.5")
Using 3 Hinges	61kg(135lbs)	890mm(35")



732-4 135° Glass to Glass Hinge




734-4 90° Glass to Glass Hinge

SHOWER DOOR HINGES 700-3A SERIES



720-3AWall Mount Hinge,
Full Plate

722-3AWall Mount Hinge,
Offset Back Plate
Available on request



730-3A 180° Glass to Glass Hinge



732-3A 135° Glass to Glass Hinge



734-3A 90° Glass to Glass Hinge

700-3A SERIES OF HINGES

700-3A Series of Hinges have rectangular design with beveled edges and round corners but are strengthened for 8-12mm (5/16"-1/2") thick glass provide bigger mounting surface on glass and can be also side mounted at top and bottom corners of the door besides anywhere in-between.

SPECIFICATIONS:

■ Hinge Size: 110x70mm(4-5/16"x2-3/4")

Construction:

Solid Brass

Hinge Swings:

90° in and 90° out.

Closing Type:

Self-Centering when within 25° of closed position

Cut-out and Hole Required

Standard Scope of Supply Includes:

Gaskets, Self Drilling Screws & Plastic Anchor Bolts for Wall Mount Hinges and Glass Cut Out Drawing.

Standard Finishes:

CP (Bright Chrome), BN (Brushed Nickel), SCP (Satin Chrome), BSCP (Brushed Satin Chrome), AB (Antique Brass), PB (Polished Brass), ORB (Oil Rubbed Bronze), GM (Gun Metal), Ti(Titanium plated), PVD.

Maximum Capacities

Quantity of Hinges	Door Weight	Door Width
Using 2 Hinges	40kg(90lbs)	800mm(31.5")
Using 3 Hinges	61kg(135lbs)	890mm(35")



720 - 3

Wall Mount Hinge,

H Plate

SHOWER DOOR HINGES 700-3 SERIES

700-3 SERIES OF HINGES 700-3 Series of

700-3 Series of Hinges have rectangular design with beveled edges and round corners, provide bigger mounting surface on glass and can be also side mounted at top and bottom corners of the door besides anywhere in-between. They can be used to support 8-12mm (5/16"-1/2") thick safety glass in swinging door installations.





730-3 180° Glass to Glass Hinge

SPECIFICATIONS:

Hinge Size:

 $110 \times 60 \text{mm} (4-5/16" \times 2-3/8")$

Construction:

Solid Brass

Hinge Swings:

90° in and 90° out.

Closing Type:

Self Closing precisely to 0°


Cut-out and Hole Required

Standard Scope of Supply Includes:

Gaskets, Self Drilling Screws & Plastic Anchor Bolts for Wall Mount Hinges and Glass Cut Out Drawing.

Standard Finishes:

CP (Bright Chrome), BN (Brushed Nickel), SCP (Satin Chrome), BSCP (Brushed Satin Chrome), AB (Antique Brass), PB (Polished Brass), ORB (Oil Rubbed Bronze), GM (Gun Metal), Ti(Titanium plated), PVD.



Quantity of Hinges	Door Weight	Door Width
Using 2 Hinges	40kg(90lbs)	780mm(31")
Using 3 Hinges	61kg(135lbs)	860mm(34")



732-3 135° Glass to Glass Hinge



734-3 90° Glass to Glass Hinge



SHOWER DOOR HINGES 700-2A SERIES

700-2A SERIES OF HINGES:

700-2A Series of Hinges also have rounded design but are strengthened to support 8-12mm (5/16''-1/2'') thick glass.





720-2AWall Mount Hinge,

Full Back Plate

7 22-2A
Wall Mount Hinge,
Offset Back Plate
available

SPECIFICATIONS:

■ Hinge Size:

105x70mm(4-1/8"x2-3/4")

Construction:

Solid Brass

Hinge Swings:

90° in and 90° out.

Closing Type:

Self-Centering when within 25° of closed position





Standard Scope of Supply Includes:

Gaskets, Self Drilling Screws & Plastic Anchor Bolts for Wall Mount Hinges and Glass Cut Out Drawing.



732-2A 135° Glass to Glass Hinge

Standard Finishes:

CP (Bright Chrome), BN (Brushed Nickel), SCP (Satin Chrome), BSCP (Brushed Satin Chrome), AB (Antique Brass), PB (Polished Brass), ORB (Oil Rubbed Bronze), GM (Gun Metal), Ti(Titanium plated), PVD.



734-2A 90° Glass to Glass Hinge

Maximum Capacities

Quantity of Hinges	Door Weight	Door Width
Using 2 Hinges	40kg(90lbs)	760mm(30")
Using 3 Hinges	55kg(120lbs)	820mm(32")
· NOTE D		

SHOWER DOOR HINGES 700-2 SERIES

Wall Mount Hinge. Offset Back Plate




SPECIFICATIONS:

700-2 SERIES OF

700-2 Series of Hinges have rounded design. They can be used to

(1/4''-5/16'') thick

HINGES



support 6-8mm

safety glass in

swinging door installations.

 $95 \times 70 \text{mm} (3-3/4" \times 2-3/4")$



Solid Brass

Hinge Swings:

90° in and 90° out.

Closing Type:

Self Closing

Cut-out and Hole Required

Standard Scope of Supply Includes:


Gaskets, Self Drilling Screws & Plastic Anchor Bolts for Wall Mount Hinges and Glass Cut Out Drawing.

Standard Finishes:

CP (Bright Chrome), BN (Brushed Nickel), SCP (Satin Chrome), BSCP (Brushed Satin Chrome), AB (Antique Brass), PB (Polished Brass), ORB (Oil Rubbed Bronze), GM (Gun Metal), Ti (Titanium plated), PVD.

Maximum Capacities

Quantity of Hinges	Door Weight	Door Width
Using 2 Hinges	27kg(60lbs)	720mm(28")
Using 3 Hinges	41kg(90lbs)	820mm(32")



730-2 180° Glass to Glass Hinge



732-2 135° Glass to Glass Hinge



734 - 290° Glass to Glass Hinge



SHOWER DOOR HINGES 700S SERIES

720S
Wall Mount Hinge,
Full Back Plate

722S

Wall Mount Hinge, Offset Back Plate available

700S SERIES OF HINGES:

700S Series of Hinges are Junior Size Hinges designed with beveled edges and radius corners. They can be used to support 6-8mm (1/4"-5/16") thick safety glass in swinging door installations.



730S 180° Glass to Glass Hinge

SPECIFICATIONS:

Hinge Size:

75x46mm(2-15/16"x1-13/16")

Construction:

Solid Brass


Hinge Swings:

90° in and 90° out.

Closing Type:

Self-Centering when within 25° of closed position

Cut-out Required



Gaskets, Self Drilling Screws & Plastic Anchor Bolts for Wall Mount Hinges and Glass Cut Out Drawing.

Standard Finishes:

CP (Bright Chrome), BN (Brushed Nickel), SCP (Satin Chrome), BSCP (Brushed Satin Chrome), AB (Antique Brass), PB (Polished Brass), ORB (Oil Rubbed Bronze), GM (Gun Metal), Ti(Titanium plated), PVD.



732S

135° Glass to Glass Hinge



734S 90° Glass to Glass Hinge

Maximum Capacities

Quantity of Hinges	Door Weight	Door Width
Using 2 Hinges	27kg(60lbs)	710mm(28")
Using 3 Hinges	40kg(90lbs)	810mm(32")

SHOWER DOOR HINGES 700S-1 SERIES

700S-1 SERIES OF HINGES:

720S-1
Wall Mount Hinge,
Full Back Plate
722S-1


Wall Mount Hinge, Offset Back Plate available



SPECIFICATIONS:

Hinge Size:

 $75 \times 46 \text{mm} (2-15/16" \times 1-13/16")$



Solid Brass

Hinge Swings:

90° in and 90° out.

Closing Type:

Self-Centering when within $25\,^\circ$ of closed position

Cut-out Required

Standard Scope of Supply Includes:


Gaskets, Self Drilling Screws & Plastic Anchor Bolts for Wall Mount Hinges and Glass Cut Out Drawing.

Standard Finishes:

CP (Bright Chrome), BN (Brushed Nickel), SCP (Satin Chrome), BSCP (Brushed Satin Chrome), AB (Antique Brass), PB (Polished Brass), ORB (Oil Rubbed Bronze), GM (Gun Metal), Ti(Titanium plated), PVD.

Maximum Capacities

Quantity of Hinges	Door Weight	Door Width
Using 2 Hinges	27kg(60lbs)	710mm(28")
Using 3 Hinges	40kg(90lbs)	810mm(32")



730S-1 180° Glass to Glass Hinge



732S-1 135° Glass to Glass Hinge



734S-1 90° Glass to Glass Hinge



SHOWER DOOR HINGES 700S-3A SERIES



720S-3A
Wall Mount Hinge,
Full Back Plate
722S-3A

Wall Mount Hinge, Offset Back Plate available



730S-3A 180° Glass to Glass Hinge



732S-3A 135° Glass to Glass Hinge



734S-3A 90° Glass to Glass Hinge

700S-3A SERIES OF HINGES:

700S-3A Series of Hinges are Junior Size Hinges of rectangualar shape with beveled edges and radius corners.
They can be used to support 6-8mm (1/4"-5/16") thick safety glass in swinging door installations.

SPECIFICATIONS:

■ Hinge Size: 85x60mm(3-3/8"x2-3/8")

Construction:

Solid Brass

Hinge Swings:

90° in and 90° out.

Closing Type:

Self Closing precisely to 0°

Cut-out and Hole Required

Standard Scope of Supply Includes:

Gaskets, Self Drilling Screws & Plastic Anchor Bolts for Wall Mount Hinges and Glass Cut Out Drawing.

Standard Finishes:

CP (Bright Chrome), BN (Brushed Nickel), SCP (Satin Chrome), BSCP (Brushed Satin Chrome), AB (Antique Brass), PB (Polished Brass), ORB (Oil Rubbed Bronze), GM (Gun Metal), Ti (Titanium plated), PVD.

Maximum Capacities

Quantity of Hinges	Door Weight	Door Width
Using 2 Hinges	27kg(60lbs)	710mm(28")
Using 3 Hinges	40kg(90lbs)	810mm(32")
Using 3 miliges	+0Kg(50155)	0 1011111





SHOWER DOOR HINGES 700S-2A SERIES



720S-2A

Wall Mount Hinge, Full Back Plate

722S-2A

Wall Mount Hinge Offset Back Plate available



730S-2A

180° Glass to Glass Hinge



732S-2A

135° Glass to Glass Hinge



734S-2A

90° Glass to Glass Hinge

700S-2A SERIES OF HINGES:

700S-2A Series of Hinges are Junior Size Hinges of rounded design. They can be used to support 6-8mm (1/4"-5/16") thick safety glass in swinging door installations.

SPECIFICATIONS:

■ Hinge Size:

 $85 \times 60 \, \text{mm} \, (3-3/8'' \times 2-3/8'')$

Construction:

Solid Brass

Hinge Swings:

90° in and 90° out.

Closing Type:

Self Closing precisely to 0°

Cut-out and Hole Required

Standard Scope of Supply Includes:

Gaskets, Self Drilling Screws & Plastic Anchor Bolts for Wall Mount Hinges and Glass Cut Out Drawing.

Standard Finishes:

CP (Bright Chrome), BN (Brushed Nickel), SCP (Satin Chrome), BSCP (Brushed Satin Chrome), AB (Antique Brass), PB (Polished Brass), ORB (Oil Rubbed Bronze), GM (Gun Metal), Ti(Titanium plated), PVD.

■ Maximum Capacities

- maximum output		
Quantity of Hinges	Door Weight	Door Width
Using 2 Hinges	27kg(60lbs)	710mm(28")
Using 3 Hinges	40kg(90lbs)	810mm(32")

